

ORDERING GUIDE FOR THE ELIMINATOR HD ACTUATOR

Ordering Information

Base No. (Capacity)	Unit Mounting Option	Motor Position	Precision/Lead Accuracy**
HD201 (1,000 lbf)	MB: Bottom Mount	1, 2, 3, 4	A: .002 in/ft Zero Backlash
HD302 (2,000 lbf)	FF: Front Flange	0 = In-Line	B: .0005 in/ft Zero Backlash
HD304 (4,000 lbf)	MF: Foot Mount		X: Standard
HD404 (4,000 lbf)	TF: Front Trunnion		
HD406 (6,000 lbf)	TR: Rear Trunnion		
HD508 (8,000 lbf)			
HD516 (16,000 lbf)			
HD618 (18,000 lbf)			
HD625 (25,000 lbf)			

Std. Stroke Length*	Rod End Option	Gearbelt Reduction	N.C. Switch Qty
06: 6 in.	E: Female Eye	00: In-Line/Direct Coupled	0, 1, 2, 3, etc.
12: 12 in.	F: Female Thread	10: 1:1	
18: 18 in.	A: Self-Aligning Coupler	20: 2:1	
24: 24 in.	M: Male Thread		
30: 30 in.	S: Spherical Rod Eye		
36: 36 in.			
42: 42 in.			
48: 48 in.			

Configuration	Switch Type	N.O. Switch Qty
L: In-Line	A: Hall Sourcing PNP	0, 1, 2, 3, etc.
U: Parallel Offset	B: Hall Sinking NPN	
	C: Reed	
	D: Switch Track / No Switches	
	X: Solid Cover / No Switches	

For custom stroke lengths, contact EDrive.

* HD201 is available with stroke lengths up to 12 in.

HD302 – HD304 are available with stroke lengths up to 36 in.

HD404 – HD406 are available with stroke lengths up to 42 in.

HD508 – HD625 are available with stroke lengths up to 48 in.

** HD201 – Std. Precision/Lead Accuracy is 0.0005 in/ft, Zero Backlash

** HD302, HD404 – Zero Backlash not available