

ORDERING GUIDE FOR THE TAC LS ACTUATOR

Ordering Information

Base No. (Capacity)	Unit Mounting Option	Motor Position	N.C. Switch Qty
LS204 (400 lbf)	MB: Bottom Mount	1, 2, 3, 4	0, 1, 2, 3, etc.
LS209 (900 lbf)	MF: Foot Mount	0 = In-Line	
LS305 (500 lbf)	CR: Rear Clevis**		
LS310 (1,000 lbf)	FF: Front Flange**		
LS320 (2,000 lbf)	TF: Front Trunnion**		
	TR: Rear Trunnion**		

Std. Stroke Length*	Rod End Option	Gearbelt Reduction	Switch Type
24: 24 in.	E: Female Eye	00: In-Line/Direct Coupled	A: Hall Sourcing PNP
30: 30 in.	F: Female Thread	10: 1:1	B: Hall Sinking NPN
36: 36 in.	A: Self-Aligning Coupler	20: 2:1	C: Reed
42: 42 in.	M: Male Thread		X: No Switches
48: 48 in.	S: Spherical Rod Eye		
54: 54 in.			
60: 60 in.			

Configuration
L: In-Line
U: Parallel Offset

For custom stroke lengths, contact EDrive.

* LS204 – LS209 are available with stroke lengths up to 36 in.

LS305 – LS320 are available with stroke lengths from 30 in. to 60 in.

** Vertical Mounting Only